

TECHNICAL DOCUMENT

PRODUCT SELECTION GUIDE

When using the DirecTV® 5 LNB Ka/Ku Band System:

<i>Model Number:</i>	<i>Description:</i>
WBS41202NF	for distribution up to twelve receivers for any DirecTV system
WBS41602NF	for distribution up to sixteen receivers for any DirecTV system

When distributing to over 16 receivers for the DirecTV® systems:

<i>Model Number:</i>	<i>Description:</i>
WBA425F	a 25dB amplifier that must start a trunk and tap system
WBT110F or WBT410F	these are single or four way taps that are used to branch off the main trunkline in a system. Four of the WBT 110F's or one of the WBT410F are used for every multiwitch in the system.
WBS41202NF or WBS41602NF	for distribution up to twelve or sixteen receivers per tap

Please refer to www.satelliteusaelectronics.com for design help. Click examples for layouts using this equipment.

Please refer to www.satelliteusaelectronics.com for design help. Click examples for layouts using this equipment.

When the installation has long cable runs:

WBA425F	DirecTV system. This amplifier compensates for up to 315ft of RG6 cable and is a four input/four output model.
WBA125F	DirecTV system. This amplifier compensates for up to 315ft of RG6 cable and is a single input/single output model.

When using a DishNetwork DishPro® or BellExpressVu system:

SLA5530NF	a 30dB amplifier that must start all DishNetwork systems
DMK55124F	a twelve way cascable multiswitch for DishNetwork systems

Please refer to www.satelliteusaelectronics.com for design help. Click examples for layouts using this equipment.