

WIDE BAND MULTISWITCHES

WBS41202NF & WBS 412602NF

12 & 16-Way Wide Band Multiswitches

Satellite USA offers the new Ka/Ku band multiswitch that is compatible with the new 5 LNB DirecTV system . The WBS multiswitches are available in twelve and sixteen output models which can be used in all DirecTV installations. The Satellite USA multiswitches come with weatherproof housing and are powered remotely via RG-6 coax cable. They do not have a terrestrial input because the satellite signal is now being distributed from 250 to 2200 MHz. The WBS multiswitches are amplified and provide up to a 5 dB gain.

FREQUENCY RANGES		
WBS41202NF	250 ... 2200 MHz (SAT-IF)	
WBS41602NF	250 ... 2200 MHz (SAT-IF)	
THROUGH LOSS		
WBS41202NF	5dB @ 250MHz	+5dB @ 2200MHz
WBS41602NF	5dB @ 250MHz	+5dB @ 2200MHz
ISOLATION OF TAPS		
WBS41202NF	>30dB	
WBS41602NF	>30dB	
POWER SUPPLY		
WBS41202NF	320 mA @ 19V	
WBS41602NF	320 mA @ 19V	

NOISE FIGURE		
WBS41202NF	7dB	
WBS41602NF	7dB	
MAX OUTPUT LEVELS		
WBS41202NF	250 ... 2200 MHz	-13.75 dBm
WBS41602NF	250 ... 2200 MHz	-13.75 dBm
PRODUCT DIMENSIONS		
WBS41202NF	5.19" (W) X 7.28" (H) X 1.41" (D)	
WBS41602NF	5.19" (W) X 7.28" (H) X 1.41" (D)	
CURRENT CONSUMPTION		
WBS41202NF	300 mA (Max Remote Current)	
WBS41602NF	300 mA (Max Remote Current)	



SATellite
USA

 **Lead Free**
Made in Germany

325 LOC CANOE CIRCLE
STEVENSVILLE, MD 21666
TEL:410.643.6535

WEB:WWW.SATELLITEUSA.ELECTRONICS.COM